



## MATERIAL SPECIFICATION



# HydraCX<sup>2</sup>

## Extreme Slope Matrix

The North American Green HydraCX<sup>2</sup> Extreme Slope Matrix shall be a hydraulically-applied matrix composed of a patent-pending blend of mechanically processed straw fibers, reclaimed cotton plant material, performance-enhancing tackifiers, and other proprietary additives. The HydraCX<sup>2</sup> requires no curing for soil erosion protection, and establishes an intimate bond upon application with the soil's surface to create a continuous, porous, absorbent and flexible erosion control matrix that allows for rapid germination and accelerated plant growth. The HydraCX<sup>2</sup> mulch is biodegradable and consists of approximately 90% organic matter.

The all natural fiber mulch shall satisfy the control performance criteria set forth in the Ceriodaphnia dubia, Daphnia magna and Pimephales promelas tests as described in EPA documentation (USEPA 2002) and the Region VIII NPDES Whole Effluent Toxics Control Program (EPA Region VIII 1997); therefore illustrating no significant toxicity for the mulch.

### Composition:

All components of the HydraCX<sup>2</sup> mulch shall be pre-packaged by the Manufacturer to assure material performance and in compliance with the following values. **Under no circumstances will field mixing of additives or components be accepted.**

Mechanically processed Straw – 65% ± 3%

Mechanically processed Reclaimed Cotton Plant Material– 25 % ± 3%

Proprietary Hydro-Colloid Tackifiers and Activators – 10% ± 1%

### Specifications:

Content: Straw/Reclaimed Cotton Plant Material

Packaging: 50 lbs (23 kg) +/- 3%

Total Organic Matter: 90.0

Carbon to Nitrogen Ratio: 38:1\*

Moisture Content: 12% ± 3%

Color: Natural Green

\* Analysis concluded from a representative sample as the C:N Ratio may vary from sample to sample.

### Packaging:

Bags are filled with 50 lbs (23 kg) of material and packaged in a UV and weather-resistant bag. Each pallet contains 40 bags or one ton with a plastic pallet cover for enhanced protection from rain and UV rays.

### Manufacturing:

HydraCX<sup>2</sup> is manufactured exclusively for North American Green by Mulch & Seed Innovations, LLC, Centre, Alabama. HydraCX<sup>2</sup> is manufactured within a set of quality guidelines established after years of product development and rigorous testing in varying conditions.

### Application Instructions\*:

1. Fill tank of a mechanically agitated hydroseeding machine with sufficient water to suspend seed and fertilizers. Add soil amendments.
2. Continue to add water slowly while adding HydraCX<sup>2</sup> at a steady rate. Use loading chart to determine the proper application rates. Mix at a rate of 50 lbs of HydraCX<sup>2</sup> per 100 gallons of water.
3. Agitate for a minimum of 10 minutes after adding the last amount of water and HydraCX<sup>2</sup>.
4. Apply in a uniform layer from 2 opposing directions to ensure complete soil coverage. Irregular surfaces may need slightly higher application rates to obtain adequate coverage.
5. Clean equipment properly to ensure HydraCX<sup>2</sup> is removed from the pump, tank, and hoses.

Not for use in channels, swales, or other areas where concentrated flows are anticipated, unless installed in conjunction with a temporary erosion control blanket or permanent reinforcement mat. HydraCX<sup>2</sup> may be applied on saturated surfaces.

Do not allow foot traffic or grazing on treated areas until vegetated. Be cautious of slippery surfaces while applying.

Warning: Do not store near an open flame or heat source. Use caution when stacking units.

\* See Installation guide for more detailed information regarding application of the HydraCX<sup>2</sup>