

THE NATURAL PROGRESSION

Lock Down Your Blown Straw | Contains 100% Natural Fibers
No Additional Binders Needed | Specifically Formulated to Bind Blown Straw
No Additional Infield Mixing Required | Easy to Apply over Blown Straw

UISIT: www.hydrostraw.com



Application Pates Ibs/ac Locking Down Blown 750-1,500 Straw Hose Work:

60lbs per 100 Gallons Tower Work: 75lbs per 100 Gallons

Mixture Rates







HydroStraw® Straw Lock: Our objective is to produce long pliable straw fibers that have been through our Heat & Mechanically Treated Process HMT™ that allows them to interact with the paper, organic fibers and glues to lock the blown application of fibers together. The paper component is added to take advantage of the paper mache process allowing the matrix to lock the straw in place.

HydroStraw® Straw Lock: The goal is to cover and coat the conventionally blown straw together to reduce its ability to be removed by the wind. The blown straw is in contact with the soil. The HydroStraw Straw Lock is to be applied in a high viscosity slurry to keep the slurry in contact with the blown straw. Please visit website at www.hydrostraw.com for Application Methods Recommendations.

PRODUCT COMPOSITION

Heat & Mechanically Treated (HM™) Straw	66.0% +/- 1.0%
Proprietary Crossed-Linked Trackifier	4.0% +/- 1.0%
Natural Fiber for Matrix Entanglement	10.0% +/- 1.0%
Paper	10.0% +/- 1.0%
Moisture Content	

Please note HydroStraw® Straw Lock is specifically designed and formulated as a secondary Lock Down application over blown straw. Its enhanced formulation is not designed to be used as a conventional hydraulic mulch







info@maritimehydroseed.com

242010 © 2011 All Rights Reserved. Created By: Ignitra Marketing Group, LLC ∙ info@ignitra.com ∙ www.ignitra.com