



MPT

PERFORMANCE PRODUCTS FOR HYDRO-SEEDING PROFESSIONALS

- MEETS OR EXCEEDS REQUIREMENTS FOR NON-ASPHALTIC TACKING EMULSIONS
- CONTAINS POLY-ACRYLAMIDE AND HYDRO-COLLOID POLYMERS
- HIGH VISCOSITY MULTI-PURPOSE TACKIFIER FOR BINDING FIBER MULCH AND STRAW MULCH

DIRECTIONS FOR USE

ONCE YOUR HYDRAULIC SEEDER IS APPROXIMATELY 1/3 FULL OF WATER ADD MPT, SEED, FIBER MULCH & FERTILIZER TO THE SLURRY. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.

PHYSICAL PROPERTIES

pH RANGE 7.0 +- 1 SPECIFIC GRAVITY .8298

APPLICATION RATE

FIBER MULCH BINDING

MODEST TO 4 TO1 SLOPE 75 LBS PER ACRE
3 TO 1 SLOPE 100 LBS PER ACRE
> 2 TO 1 SLOPE 150 LBS PER ACRE

STRAW MULCH BINDING 150 LBS PER ACRE

PACKAGING

12 & 50 LB BAGS, FOUR (12) POUND BAGS PER CASE, SHIPPED 40 CASES PER 48 x 48 PALLET





DISTRIBUTED BY



www.maritimehydroseed.com 506.672.1600 info@maritimehydroseed.com